Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: as - Schwabe Supplier's address: Produktmanagement, Merkurstr. 10, 72184 Eutingen im Gäu, DE Model identifier: 46347 Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type SMD (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: No Product parameters Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°s), in a wide cone (120°) or in a narrow cone (90°) Unique power (Pom), expressed in W and rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of CRI-willian be second decimal second decimal conditions of the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest integer, or the range of CRI-values that can be set to the nearest	sources		, ,	_			
Model identifier: 46347 Type of light source: LED Non-directional or directional: NDLS Light source cap-type (or other electric interface) SMD (or other electric interface) NMLS Connected light Nein source (CLS): Nein source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: No Anti-glare shield: Nein Dimmable: No Product parameters Value Parameter Value General product parameters: Energy consumption in omode (kWh/1000 h), rounded up to the nearest integer 60 Energy efficiency class F Useful luminous flux (фuse), in a wide cone (120°) in a narrow cone (90°) in a narrow cone (90°). In a wide cone (120°) or in a narrow cone (90°). In a wide cone (120°) or in a narrow cone (90°). Standby power (Pth), or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal index, rounded to the second decimal index, rounded to the nearest index, or the range of CRI-values that can be set Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal index, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions without Depth Width - Spectral power of Spectral power in last page	Supplier's name	e or trade mark:	as - Schwabe				
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: High luminance light source: Nein Anti-glare shield: Parameter Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (3609), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal Outer Height Outer Height Outer Height Outer Height Outer Height Depth AMMLS Connected light Noein Standby expressed in W and rounded to the nearest integer, or the range of CRI-values that can be set Outer Height Depth On-mode Depth ANDLS Non-directional: Nein Dimmable: No Product parameter Value Parameter Value Parameter Value Energy efficiency F class Useful luminous flux (фuse), at 800 in Wide cone (120°) Energy efficiency F class Value Correlated colour temperature, rounded to the nearest 100 K, or the range of Correlated colour temperatures, rounded to the nearest 100 K, or the range of CRI-values that can be set Outer Height Outer Height Depth Outer Height Depth A80 Nein Dimmable: No Energy efficiency F Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions Width Depth Depth A80 Nein Dimmable: No Correlated colour temperatures, rounded to the nearest integer, or the range of CRI-values that can be set Outer distribution in the in last page	Supplier's address: Produktmanagement, Merkurstr. 10, 72184 Eutingen im Gäu, DE						
Lighting technology used: LED Non-directional or directional or directional: Light source cap-type SMD (or other electric interface) Mains or non-mains: NMLS Connected light Nein source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: Product parameters Parameter Value Parameters Parameter Value Parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful Luminous flux (фuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), 60,0 Standby power (Psb), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal in last page in last page	Model identifier: 46347						
Light source cap-type SMD	Type of light so	urce:					
Cor other electric interface) Mains or non-mains: NMLS Connected light Source (CLS):	Lighting techno	logy used:	LED		NDLS		
Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: High luminance light source: Nein Anti-glare shield: Parameter Value Parameters Parameter Value Parameter Value Parameter: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360%), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Alter and be set On-mode power (Pon), expressed in W And rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked thandby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal in last page in last page	Light source cap-type		SMD				
Source (CLS): Colour-tuneable light source: High luminance light source: Anti-glare shield: Nein Product parameters Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pan), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height General product parameters Energy efficiency class Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pan), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal index, rounded to the secon	(or other electri	ic interface)					
High luminance light source: Anti-glare shield: Nein Product parameters Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°s), in a wide cone (120°) or in a narrow cone (90°s) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal for CLS, expressed in W and rounded to the second decimal for CLS, expressed in W and rounded to the second decimal for CLS, expressed in W and rounded to the second decimal for CLS for CLS, expressed in W and rounded to the second decimal for CLS for	Mains or non-m	nains:	NMLS		Nein		
Anti-glare shield: Nein Product parameters Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°s), in a wide cone (120°) or in a narrow cone (90°s) On-mode power (Pon), expressed in W On-mode power (Pon), expressed in W No No Energy efficiency class F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked the second decimal in last page	Colour-tuneable	e light source:	Nein	Envelope:	-		
Product parameters Parameter Value Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for Clour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions without full for the parameters: Energy efficiency class set fill we follow the second decimal full for the parameters integer. F Colour rendering in W and rounded to the nearest integer, or the range of CRI-values that can be set in last page in last	High luminance	light source:	Nein				
Parameter Value Parameter Value	Anti-glare shield	d:	Nein	Dimmable:	No		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal Spectral power (Pont) or the range of CRI-values that can be set Outer dimensions Width Depth Depth Outer dimensions Width Depth Outer dimensions Width Depth Outer dimensions Width Outer dimensions Width Depth Outer dimensions Width Outer dimensions Width Depth Outer dimensions Width Outer distribution in the distribu	Product parameters						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer dimensions Width Outer dimensions Width Depth Oscillated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set Octobrea Class Correlated colour temperature, rounded to the nearest 100 K, that can be set Octobrea Class Correlated colour temperature, rounded to the nearest 100 K, that can be set Octobrea Class Correlated colour temperature, rounded to the nearest 100 K, or the range of CRI-values that can be set Outer dimensions Width Depth Octobrea Class Correlated colour temperature, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions Width Octobrea Class A 800 in Wide Correlated colour temperature, rounded to the nearest into the nearest into the nearest into the nearest into the nearest integer, or the range of CRI-values that can be set Outer dimensions Width Outer distribution in the in last page	Parameter		Value	Parameter	Value		
mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the nearest integer, or the range of CRIvalues that can be set Outer Height for CLS, expressed in Width for the present integer, or the range of CRIvalues that can be set Outer Height for CLS, expressed in Width for the present integer, or the range of CRIvalues that can be set	General product parameters:						
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal Networked tandby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer dimensions without Emperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set October 100 Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions without Depth Cone (120°) Emperature, rounded to the nearest 100 K, that can be set October 100 Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions without Depth Cone (120°) Emperature, rounded to the nearest 100 K, or the range of CRI-values that can be set Spectral power See image distribution in the in last page	mode (kWh/1000 h), rounded		60	, ,	F		
expressed in W and rounded to the second decimal Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal Networked standby power (P _{net}) for CLS, expressed in W and index, rounded to the nearest integer, or the range of CRI-values that can be set Outer dimensions Width Depth Expressed in W and rounded to the second decimal Solution in W and rounded to the second decimal Solution in W and rounded to the second decimal Solution in W and rounded to the second decimal A solution in W and rounded to the second decimal Solution in W and rounded to the second decimal A sol	indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone		cone (120°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set			
for CLS, expressed in W and rounded to the second decimal index, rounded to the nearest integer, or the range of CRI-values that can be set Outer Height - Spectral power dimensions Width - distribution in the in last page without Depth -	1 (01177		60,0	expressed in W and rounded to the	0,00		
dimensions Width - distribution in the in last page Depth -	for CLS, expressed in W and		-	index, rounded to the nearest integer, or the range of CRI- values that can be	80		
without Depth -		Height	-	·	See image		
Deptil -		Width	-	distribution in the	in last page		
	without	Depth	-		Seite 1 / 2		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,313			
		coordinates (x and y)	0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	10	Survival factor	-			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;